



21.15.090.C Architectural Styles - GOOGIE

Standard		Applicant Response			Planning Staff Only	
		☐	Page #	Response – Provide a brief description	☐	Explanation (if not marked as complete)
C	Architecture					
C.1	All buildings utilizing the Googie style shall include the following:					
	Flat or low-sloped (3:12 or less) rooflines	☐			☐	
	Cantilevered roof eaves (at least three (3') feet long	☐			☐	
	At least one (1) elevation shall include an upswept roof line	☐			☐	
	Large sheet glass windows (minimum six (6') any dimension)	☐			☐	
	Exposed steel beams and/or columns	☐			☐	
	At least fifteen (15) percent of the primary street elevation shall be composed of Palo Verde Stone, flag-stone, aggregate stone panels, or glossy-glazed brick from ground to eave	☐			☐	
C.2	In addition to the above, Googie projects shall include at least two (2) of the following features; mixed-use projects eleven (11) units or more and commercial developments over 25,000 square feet shall include at least three (3) of the following features					
	A pylon or pole sign which penetrates the eave/roofline, where allowed per Ch 30.33	☐			☐	
	At least one (1) wall-form between five (5) and fifteen (15) degree angle	☐			☐	
	Decorative architectural medallions at least three (3') in diameter representing starbursts, atomic symbols, boomerangs, or amoebae shapes	☐			☐	
	Exterior globe- or cylinder-shaped light fixtures	☐			☐	
	Exterior terrazzo steps/flooring/ patio at the primary entry	☐			☐	
	Repetitive diamond-shaped eave details	☐			☐	
	Zig-zag roof lines	☐			☐	